



io6 Pro

≠ratio

BUSINESS CHARGING

- Available in 7.4kW or 22kW
- Integrated MID-Certified Power Meter
- # Built-in single and three phase open PEN fault protection
- #4G connectivity as standard
- Easy Installation
- Fast Bluetooth commissioning
- # Socketed or 7.5m type 2 cable
- Power sharing up to 32 devices
- # OCPP 1.6J compliant
- **#** RFID reader
- # UK based support team



io6 PRO

ratioev.uk

| Dimensions and Specifications | | |
|-------------------------------|---|--|
| Charging System | IEC 61851 Mode 3 | |
| Power Input | Single phase / three phase, 230 /400v, 32A | |
| Power Output | 7.4kW or 22kW | |
| Protections | DC 6mA | |
| Pen Fault Detection | Open PEN fault protection on single and three phase | |
| Dimensions and Specifications | 400mm x 250mm x 105mm | |
| Weight | 4kg | |
| Impact Rating | IK08 | |
| Enclosure Rating | IP54 | |
| Operating Temp. | -25C to +40C | |
| Connectivity | Ethernet, Wi-Fi and 4G sim card and 36 months data supplied as standard | |
| OCPP | OCPP 1.6J compliant | |
| Marking | UKCA | |
| | | |

| Design Features | |
|-------------------------|--|
| Housing | PC/ABS-VO |
| Options | Single phase 7.4kW to three phase 22kW options |
| Energy Meter | Built in certified MID meter |
| Applications | Suitable for domestic, business, commercial and fleet |
| Variants | Socketed or 7.5m cable options available |
| Power Sharing* | Connect up to 32 chargers on one mains connection. Available power will be distributed evenly to connected EVs. Supports static and dynamic load management. |
| Solar Charging* | Prioritises your power consumption by utilising solar energy when available |
| Safety Feature | Locking mechanism to prevent disconnection of cable under load |
| Commissioning | Full configuration of the charger via Bluetooth using the Ratio app, with settings stored in the Ratio cloud |
| Multi User | Multi charger, Multi EV. Manage access and session for all users, chargers and EVs |
| Secure authentication | Protect your charger from unauthorised use using the Ratio app, alternatively use the plug and charge mode for fast and easy access. CPO/CPMJ |
| Configurable cable lock | Option to lock the cable into the charger |
| Radar Detection | io6 Pro Lux variant includes a white light to detect motion up to 5 metres away from the charger |
| UV Light | io6 pro Lux variant includes UV light which works in conjuntion with Ratio UV cable to light up the area for user safety |
| Ratio App | Provides full control and visibility over your charging sessions (Android And iOS). Allows user to schedule charging to make use of cheaper tariffs |
| | |

| Compliance | |
|------------|--|
| Standards | LVD 2014/35/EU, EMCD 2014/30/EU, BS EN61851-2019, EN61000-2, EN61000-3, CE Certified, BS7671-2018 |
| GDPR | Your privacy ad sensitive data is handled with care and in compliance with GDPR |

*Dynamic Load Management and Solar Charging requires Sense Box